


INNOVATIONS
MASTER CATALOG

TOOLING SYSTEMS
2013

www.kennametal.com






GENERAL ENGINEERING

TRANSPORTATION

www.kennametal.com



AEROSPACE & DEFENSE

EARTHWORKS

ENERGY


KM™ Quick Change Clamping System • KM80ATC™ Series



Primary Application

The KM Quick Change Clamping System is the best system on the market suitable for static, rotating, and multitasking operations. With its industry-leading design, the KM Quick Change System provides greater clamping forces than other quick-change systems. The KM Quick Change System gives you the flexibility to use KM on any application within your shop.

Features and Benefits

- KM80ATC is designed to be used on MAG Corporation VTL machines.
- KM80ATC is your solution for multitasking.





■ STA • Straight Side Mount • Metric





order number	catalog number	L1	LPR	F	HW	BW	B2	cup point socket set screw	nozzle	Nm	kg
right hand											
3545087	KM80ATCSTAR2525	45	150	33	25	25	99	MS1430	PMT04526 COOLANT NOZZLE SPRAY	55	9,51
3545089	KM80ATCSTAR3232	45	150	25	32	32	98	MS1430	PMT04526 COOLANT NOZZLE SPRAY	55	8,98
left hand											
3545088	KM80ATCSTAL2525	45	150	33	25	25	99	MS1430	PMT04526 COOLANT NOZZLE SPRAY	55	9,51
3545090	KM80ATCSTAL3232	45	150	25	32	32	98	MS1430	PMT04526 COOLANT NOZZLE SPRAY	55	8,98

■ STA • Straight Side Mount • Inch




order number	catalog number	L1	LPR	F	HW	BW	B2	cup point socket set screw	nozzle	ft. lbs.	lbs
right hand											
3480215	KM80ATCSTAR20	1.693	5.906	1.059	1.250	1.250	3.904	MS1430	PMT04526 COOLANT NOZZLE SPRAY	40	20.17
2601528	KM80ATCSTAR24	1.480	6.693	.559	1.500	1.500	3.654	MS1954	PMT04526 COOLANT NOZZLE SPRAY	90	21.44
left hand											
2628561	KM80ATCSTAL20	1.693	5.906	1.059	1.250	1.250	3.904	MS1430	PMT04526 COOLANT NOZZLE SPRAY	40	20.14
2601530	KM80ATCSTAL24	1.480	6.693	.559	1.500	1.500	3.654	MS1954	PMT04526 COOLANT NOZZLE SPRAY	90	21.44



■ **ETA • Straight End Mount • Inch**



order number	catalog number	L1	B1	F	HW	BW	B2	cup point socket set screw	nozzle	ft. lbs.	lbs
2203618	right hand KM80ATCETAR20	1.846	1.614	2.244	1.25	1.25	4	DWG MS1430	PMT04526 COOLANT NOZZLE SPRAY	40	10.32
2203619	left hand KM80ATCETAL20	1.846	1.614	2.244	1.25	1.25	4	DWG MS1430	PMT04526 COOLANT NOZZLE SPRAY	40	10.32





■ DCLN 95°

order number	catalog number	L1		F		D min		gage insert	kg
		mm	in	mm	in	mm	in		
	right hand								
2036330	KM80ATCDCLNR12KC04	70	2.756	53	2.087	106	4.17	CN..120408/CN..432	2,13
2036332	KM80ATCDCLNR16KC06	70	2.756	53	2.086	106	4.17	CN..160612/CN..543	2,24
	left hand								
2036331	KM80ATCDCLNL12KC04	70	2.756	53	2.087	106	4.17	CN..120408/CN..432	2,13
2036406	KM80ATCDCLNL16KC06	70	2.756	53	2.086	106	4.17	CN..160612/CN..543	2,24

■ Spare Parts

catalog number	shim	shim screw	clamp assembly	pin
right hand				
KM80ATCDCLNR12KC04	ICSN443	KMSP415IP	CM234R ASSY	SSP025016M
KM80ATCDCLNR16KC06	ICSN543	KMSP515IP	CM209R ASSY	SSP025018M
left hand				
KM80ATCDCLNL12KC04	ICSN443	KMSP415IP	CM234R ASSY	SSP025016M
KM80ATCDCLNL16KC06	ICSN543	KMSP515IP	CM209R ASSY	SSP025018M




■ DDJN 93°

		L1		F			
order number	catalog number	mm	in	mm	in	gage insert	kg
right hand							
2220270	KM80ATCDDJNR15KC04	70	2.7560	53	2.087	DN..150408/DN..432	1,90
2036377	KM80ATCDDJNR15KC06	70	2.7560	53	2.087	DN..150608/DN..442	1,90
left hand							
2220271	KM80ATCDDJNL15KC04	70	2.7560	53	2.087	DN..150408/DN..432	1,90
2036378	KM80ATCDDJNL15KC06	70	2.7560	53	2.087	DN..150608/DN..442	1,90

■ Spare Parts

catalog number				
	shim	shim screw	clamp assembly	pin
right hand				
KM80ATCDDJNR15KC04	IDSN443	KMSP415IP	CM234R ASSY	SSP025016M
KM80ATCDDJNR15KC06	IDSN433	KMSP415IP	CM234R ASSY	SSP025016M
left hand				
KM80ATCDDJNL15KC04	IDSN443	KMSP415IP	CM234R ASSY	SSP025016M
KM80ATCDDJNL15KC06	IDSN433	KMSP415IP	CM234R ASSY	SSP025016M




■ DDQN 107° 30'

order number	catalog number	L1		F		D min		gage insert	kg
		mm	in	mm	in	mm	in		
	right hand								
2220278	KM80ATCDDQNR15KC04	70	2.756	53	2.087	106	4.17	DN..150408/DN..432	2,07
2036379	KM80ATCDDQNR15KC06	70	2.756	53	2.087	106	4.17	DN..150608/DN..442	2,06
	left hand								
2220279	KM80ATCDDQNL15KC04	70	2.756	53	2.087	106	4.17	DN..150408/DN..432	2,07
2036380	KM80ATCDDQNL15KC06	70	2.756	53	2.087	106	4.17	DN..150608/DN..442	2,06

■ Spare Parts

catalog number				
	shim	shim screw	clamp assembly	pin
right hand				
KM80ATCDDQNR15KC04	IDSN443	KMSP415IP	CM234R ASSY	SSP025016M
KM80ATCDDQNR15KC06	IDSN433	KMSP415IP	CM234R ASSY	SSP025016M
left hand				
KM80ATCDDQNL15KC04	IDSN443	KMSP415IP	CM234R ASSY	SSP025016M
KM80ATCDDQNL15KC06	IDSN433	KMSP415IP	CM234R ASSY	SSP025016M




■ DDUN 93°


order number	catalog number	L1		F		D min		gage insert	kg
		mm	in	mm	in	mm	in		
2220286	KM80ATCDDUNR15KC04	70	2.756	53	2.087	106	4.17	DN..150408/DN..432	2,23
2036381	KM80ATCDDUNR15KC06	70	2.756	53	2.087	106	4.17	DN..150608/DN..442	2,23
2220287	KM80ATCDDUNL15KC04	70	2.756	53	2.087	106	4.17	DN..150408/DN..432	2,23
2036382	KM80ATCDDUNL15KC06	70	2.756	53	2.087	106	4.17	DN..150608/DN..442	2,23

■ Spare Parts


catalog number				
	shim	shim screw	clamp assembly	pin
right hand				
KM80ATCDDUNR15KC04	IDSN443	KMSP415IP	CM234R ASSY	SSP025016M
KM80ATCDDUNR15KC06	IDSN433	KMSP415IP	CM234R ASSY	SSP025016M
left hand				
KM80ATCDDUNL15KC04	IDSN443	KMSP415IP	CM234R ASSY	SSP025016M
KM80ATCDDUNL15KC06	IDSN433	KMSP415IP	CM234R ASSY	SSP025016M




■ MCRN 75°





order number	catalog number	L1		F		gage insert	shim	lock pin	clamp	clamp screw	kg	lbs
		mm	in	mm	in							
	right hand											
2036375	KM80ATCMCRNR19	70	2.756	48	1.890	CN..190612/CN..643	ICSN633	KLM68	CKM12	STCM4	2,29	5.06
2036376	KM80ATCMCRNR25	70	2.756	48	1.890	CN..250924/CN..866	ICSN846	KLM810	CKM24	STCM19	2,31	5.09
	left hand											
1960916	KM80ATCMCRNL19	70	2.756	48	1.890	CN..190612/CN..643	ICSN633	KLM68	CKM12	STCM4	2,29	5.06
2033887	KM80ATCMCRNL25	70	2.756	48	1.890	CN..250924/CN..866	ICSN846	KLM810	CKM24	STCM19	2,31	5.09





■ MSDN 45°




order number	catalog number	L1		F		gage insert	shim	lock pin	clamp	clamp screw	kg	lbs
		mm	in	mm	in							
2036383	KM80ATCMSDNN19	70	2.756	0	.000	SN..190612/SN..643	ISSN633	KLM68	CKM12	STCM4	1,88	4.14
2036384	KM80ATCMSDNN25	70	2.756	0	.000	SN..250924/SN..866	ISSN846	KLM810	CKM24	STCM19	1,79	3.95


■ MSKN 75°


order number	catalog number	L1		F		D min		gage insert	shim	lock pin	clamp	clamp screw	kg	lbs
		mm	in	mm	in	mm	in							
right hand														
2036385	KM80ATCMSKNR19	70	2.756	53	2.087	106	4.173	SN..190612/SN..643	ISSN633	KLM68	CKM12	STCM4	2,52	5.55
2036387	KM80ATCMSKNR25	70	2.756	53	2.087	106	4.173	SN..250924/SN..866	ISSN846	KLM810	CKM24	STCM19	2,47	5.44
left hand														
2036386	KM80ATCMSKNL19	70	2.756	53	2.087	106	4.173	SN..190612/SN..643	ISSN633	KLM68	CKM12	STCM4	2,52	5.55
1960917	KM80ATCMSKNL25	70	2.756	53	2.087	106	4.173	SN..250924/SN..866	ISSN846	KLM810	CKM24	STCM19	2,53	5.57


■ MSRN 75°



		L1		F								
order number	catalog number	mm	in	mm	in	gage insert	shim	lock pin	clamp	clamp screw	kg	lbs
2036388	right hand KM80ATCMSRNR19	70	2.756	48	1.890	SN..190612/SN..643	ISSN633	KLM68	CKM12	STCM4	2,11	4.66
2036390	left hand KM80ATCMSRNR25	70	2.756	48	1.890	SN..250924/SN..866	ISSN846	KLM810	CKM24	STCM19	2,08	4.59
2036389	KM80ATCMSRNL19	70	2.756	48	1.890	SN..190612/SN..643	ISSN633	KLM68	CKM12	STCM4	2,11	4.66
1961718	KM80ATCMSRNL25	70	2.756	48	1.890	SN..250924/SN..866	ISSN846	KLM810	CKM24	STCM19	2,08	4.59



■ MVUN 93°





order number	catalog number	L1		F		D min		gage insert	shim	lock pin	clamp	clamp screw	kg	lbs
		mm	in	mm	in	mm	in							
2036391	right hand													
	KM80ATCMVUNR16	70	2.756	53	2.087	106	4.173	VN..160408/VN..332	IVSN322	KLM34L	CKM22	STCM20	2,23	4.92
1961335	left hand													
	KM80ATCMVUNL16	70	2.756	53	2.087	106	4.173	VN..160408/VN..332	IVSN322	KLM34L	CKM22	STCM20	2,23	4.92




■ PRGC 0°




order number	catalog number	L1		F		D min		gage insert	shim	clamp screw	clamp stud	kg	lbs
		mm	in	mm	in	mm	in						
1961340	KM80ATCPRGCL20	70	2.756	53	2.087	106	4.173	RC..2006M0	169.333	121.820	119.073	1,87	4.12
3897198	KM80ATCPRGCL25	70	2.756	53	2.087	—	—	RC..2507M0..	169.337	121.820	118.404	2,08	4.58
3897200	KM80ATCPRGCL32	80	3.150	53	2.087	—	—	RC..3209M0..	169.339	121.030	118.604	2,66	5.86
2203621	KM80ATCPRGCR20	70	2.756	53	2.087	106	4.173	RC..2006M0	169.333	121.820	119.073	1,87	4.12
3897199	KM80ATCPRGCR25	70	2.756	53	2.087	—	—	RC..2507M0..	169.337	121.820	118.404	2,08	4.58
3897201	KM80ATCPRGCR32	80	3.150	53	2.087	—	—	RC..3209M0..	169.339	121.030	118.604	2,66	5.86



■ NE 93°





order number	catalog number	L1		F		D min		gage insert	clamp	clamp screw	kg	lbs
		mm	in	mm	in	mm	in					
2036394	right hand KM80ATCNER3	70	2.756	53	2.087	106	4.173	NG3L	CM73	MS2091	2,12	4.67
2036395	KM80ATCNER4	70	2.756	53	2.087	106	4.173	NG4L	CM73	MS2091	2,19	4.83
2036396	KM80ATCNER5	70	2.756	53	2.087	106	4.173	NG5L	CM81	MS1490	2,26	4.99
2036397	KM80ATCNER6 left hand	70	2.756	53	2.087	106	4.173	NG6L	CM121	MS2091	2,15	4.74
1961333	KM80ATCNEL3	70	2.756	53	2.087	106	4.173	NG3R	CM72	MS2091	2,12	4.67
1960915	KM80ATCNEL4	70	2.756	53	2.087	106	4.173	NG4R	CM72	MS2091	2,19	4.83
2036400	KM80ATCNEL5	70	2.756	53	2.087	106	4.173	NG5R	CM80	MS1490	2,26	4.99
2036398	KM80ATCNEL6	70	2.756	53	2.087	106	4.173	NG6R	CM120	MS2091	2,15	4.74



■ NS 93°





order number	catalog number	L1		F		gage insert	clamp	clamp screw	kg	lbs
		mm	in	mm	in					
3330949	right hand KM80ATCNSR3	70	2.756	53	2.087	NG3R	CM72	MS1489	2,16	4.77
2203622	KM80ATCNSR4 left hand	70	2.756	53	2.087	NG4R	CM72	MS2091	2,17	4.77
2398753	KM80ATCNLS3	70	2.756	53	2.087	NG3L	CM73	MS1489	2,16	4.77
2044321	KM80ATCNLS4	70	2.756	53	2.087	NG4L	CM73	MS2091	2,17	4.77



■ **KGME • End Mount**

										
		L1		F						
order number	catalog number	mm	in	mm	in	cartridge size	insert screw	button-head cap screw	nozzle	kg lbs
right hand										
2036392	KM80ATCKGMER50	58	2.283	41	1.594	50	MS1162	MS2002	PMT04526 COOLANT NOZZLE SPRAY	2,45 5.39
left hand										
1961339	KM80ATCKGMEL50	58	2.283	41	1.594	50	MS1162	MS2002	PMT04526 COOLANT NOZZLE SPRAY	2,45 5.39


NOTE: For A3/A4 modular blades, see the Kennametal Innovations Master Catalog Cutting Tools 2013.
Right-hand cutting units use left-hand blades.



■ **KGME • End Mount**

		L1		F						
order number	catalog number	mm	in	mm	in	cartridge size	blade screw	nozzle	kg	lbs
right hand										
3588800	KM80ATCKGMER65	57	2.24	40,5	1.595	65	MS1163	PMT04525	3,11	6.86
left hand										
3588804	KM80ATCKGMEL65	57	2.24	40,5	1.595	65	MS1163	PMT04525	3,11	6.86

NOTE: For A3/A4 modular blades, see the Kennametal Innovations Master Catalog Cutting Tools 2013.
Right-hand cutting units use left-hand blades.




■ KGMS • Side Mount



order number	catalog number	L1		F		cartridge size	blade screw	nozzle	clamp screw	kg	lbs
		mm	in	mm	in						
	right hand										
3138942	KM80ATCKGMSR50	66,5	2.618	41	1.614	50	MS1162	PMT04526 COOLANT NOZZLE SPRAY	MS2002	2,43	5.36
	left hand										
3138941	KM80ATCKGMSL50	66,5	2.618	41	1.614	50	MS1162	PMT04526 COOLANT NOZZLE SPRAY	MS2002	2,43	5.36

NOTE: For A3/A4 modular blades, see the Kennametal Innovations Master Catalog Cutting Tools 2013.
Right-hand cutting units use right-hand blades.





■ KGMS • Side Mount



order number	catalog number	L1		F		cartridge size	blade screw	nozzle	kg	lbs
		mm	in	mm	in					
	right hand									
3588790	KM80ATCKGMSR65	63,5	2.500	40	1.575	65	MS1163	PMT04525	2,81	6.20
	left hand									
3588795	KM80ATCKGMSL65	63,5	2.500	40	1.575	65	MS1163	PMT04525	2,81	6.20

NOTE: For A3/A4 modular blades, see the Kennametal Innovations Master Catalog Cutting Tools 2013.
Right-hand cutting units use right-hand blades.




■ BA • Boring Bar Adapter • Internal and External Coolant • Metric



order number	catalog number	D1	D2	L1	L9	lock screw	nozzle	wrench size clamp screw	Nm	kg
3896952	KM80ATCBA40105M	40	80	105	76	MS1947	PWZ1012	8mm	125	3,58
3897203	KM80ATCBA50130M	50	90	130	95	MS1947	PWZ1012	8mm	125	4,96

■ BA • Boring Bar Adapter • Internal and External Coolant • Inch



order number	catalog number	D1	D2	L1	L9	lock screw	nozzle	wrench size clamp screw	ft. lbs.	lbs
2024399	KM80ATCBA100276	1	2.95	2.756	2.24	—	PWZ1012	6mm	30	5.57
2024400	KM80ATCBA125295	1 1/4	3.15	2.953	2.48	—	PWZ1012	6mm	30	6.11
2024401	KM80ATCBA150413	1 1/2	3.15	4.134	2.99	MS1947	PWZ1012	8mm	90	8.04
2024402	KM80ATCBA200512	2	3.54	5.118	3.98	MS1947	PWZ1012	8mm	90	10.57

NOTE: Do not overtighten clamp screw; use torque recommendations above.
Supplied with clamp screw.
Clamp screw wrench not included.
For boring bar reducers, see page A570.



More than just the right tool • the ultimate solution.

That's **Beyond BLAST™**



That's **Different Thinking.**


At Kennametal, innovation follows vision. Our revolutionary products and services are inspired by asking “what if?” The solutions that follow — like our Beyond BLAST through-coolant inserts — deliver remarkable results in the world’s most demanding machining environments.

A cutting-edge insert that delivers coolant precisely at the cutting edge. Now that’s Different Thinking. That’s Kennametal.

To learn more about your productivity gains using Beyond BLAST technology, visit www.kennametal.com.


Milling

- Beyond BLAST technology uses low-pressure conditions to offer many of the high-pressure performance benefits.
- Delivers superior performance on titanium, using either high- or low-pressure coolant systems.
- Effective thermal management results in reduced cutting temperatures, improved lubricity, superior chip control, and longer tool life.
- Beyond BLAST for milling increases tool life by up to 300% compared with conventional coolant delivery systems.



beyond™ BLAST™

- Balanceable — fine tune with optional M6 set screws.
- Suitable for carbide and HSS cutting tools (requirements below).



Cutting Tool Shank Requirements
metric (ISO standard)

cutting tool shank diameter	tolerance	
10	h6	0,000/-0,009
12, 14, 16, & 18	h6	0,000/-0,011
20 & 25	h6	0,000/-0,013
32, 40, & 50	h6	0,000/-0,016



■ HPV TT • Metric



order number	catalog number	D1	D2	D21	L1	L2	L9	V	stop screw	wrench size stop screw	kg
3661841	KM80ATCHPVTT10090M	10	24	32	90	68	31	10	TTSS08014M	4mm	1,47
3661842	KM80ATCHPVTT10170M	10	24	32	170	63	31	10	TTSS08014M	4mm	2,02
3662743	KM80ATCHPVTT12095M	12	24	32	95	73	36	10	TTSS10014M	5mm	1,48
3662744	KM80ATCHPVTT12160M	12	24	32	160	63	36	10	TTSS10014M	5mm	1,93
3662745	KM80ATCHPVTT14095M	14	27	34	95	73	36	10	TTSS10014M	5mm	1,54
3662746	KM80ATCHPVTT16100M	16	27	34	100	78	39	10	TTSS12014M	6mm	1,55
3662747	KM80ATCHPVTT18100M	18	33	42	100	78	39	10	TTSS12014M	6mm	1,75
3662748	KM80ATCHPVTT18160M	18	33	42	160	70	39	10	TTSS12014M	6mm	2,45
3662749	KM80ATCHPVTT20105M	20	33	42	105	83	41	10	TTSS16014M	8mm	1,77
3662750	KM80ATCHPVTT25115M	25	44	53	115	93	47	10	TTSS16014M	8mm	2,34
3662751	KM80ATCHPVTT32120M	32	44	53	120	98	51	10	TTSS16014M	8mm	2,26
3662752	KM80ATCHPVTT40130M	40	60	61	130	108	51	10	TTSS20014M	10mm	3,47
3662753	KM80ATCHPVTT50140M	50	69	79	140	118	56	10	TTSS20014M	10mm	4,28

(continued)

(HPV TT continued)

Cutting Tool Shank Requirements inch (industry standard)

cutting tool shank diameter	tolerance
5/16 & 3/8	-.0001/-0.0004
7/16, 1/2, 9/16, & 5/8	.0000/-0.0004
3/4, 7/8, 1, 1-1/4, 1-1/2, & 2	.0000/-0.0005



■ HPV TT • Inch



order number	catalog number	D1	D2	D21	L1	L2	L9	V	stop screw	wrench size stop screw	lbs
3599309	KM80ATCHPVTT031335	5/16	.83	1.06	3.347	2.48	1.02	.39	TTSS06014M	3mm	3.03
3599310	KM80ATCHPVTT038630	3/8	.95	1.26	6.299	2.48	1.22	.39	TTSS08014M	4mm	4.29
3599311	KM80ATCHPVTT044374	7/16	.95	1.26	3.740	2.87	1.42	.39	TTSS10014M	5mm	3.28
3599304	KM80ATCHPVTT050374	1/2	.95	1.26	3.740	2.87	1.42	.39	TTSS10014M	5mm	3.25
3594191	KM80ATCHPVTT056374	9/16	1.06	1.34	3.740	2.87	1.42	.39	TTSS10014M	5mm	3.38
3599305	KM80ATCHPVTT062394	5/8	1.06	1.34	3.937	3.07	1.54	.39	TTSS12014M	6mm	3.41
3594317	KM80ATCHPVTT062850	5/8	1.06	1.34	8.500	2.48	1.54	.39	TTSS12014M	6mm	5.65
3594316	KM80ATCHPVTT075413	3/4	1.30	1.65	4.134	3.27	1.61	.39	TTSS16014M	6mm	3.93
3599306	KM80ATCHPVTT075630	3/4	1.30	1.65	6.299	2.76	1.61	.39	TTSS16014M	8mm	5.35
3599307	KM80ATCHPVTT088413	7/8	1.30	1.65	4.134	3.27	1.61	.39	TTSS16014M	8mm	3.84
3594315	KM80ATCHPVTT100453	1	1.73	2.08	4.528	3.66	1.85	.39	TTSS16014M	8mm	5.14
3594313	KM80ATCHPVTT125472	1 1/4	1.73	2.08	4.724	3.86	2.01	.39	TTSS16014M	8mm	4.99
3594314	KM80ATCHPVTT150512	1 1/2	2.36	2.75	5.118	4.25	2.01	.39	TTSS20014M	10mm	7.78
3599308	KM80ATCHPVTT200551	2	2.72	3.11	5.512	4.65	2.20	.39	TTSS20014M	10mm	9.37

NOTE: Do not overheat. Overheating will destroy the accuracy and functionality of the toolholder.
 Shrink Fit technical section, see page M78.
 Supplied with stop screw.
 Adjusting stop screw gage, see page M81.
 Shrink Fit accessories, see page L12–L13.
 Optional M6~1.0P x 5 lg fine balancing screw set (10 pieces) is available.
 Order number is MS1276PKG and must be ordered separately.

- 30–50% higher clamping torque compared to GP line.
- Balanceable — fine tune with optional M6 set screws.
- Suitable for carbide only, designated by groove in front face (requirements below).
- 10 kW power or greater Shrink Fit device must be used.



**Cutting Tool Shank Requirements
metric (ISO standard)**

cutting tool shank diameter	tolerance	
12, 14, 16, & 18	h6	0,000/-0,011
20 & 25	h6	0,000/-0,013
32	h6	0,000/-0,016

■ HPV TT HT • Metric



order number	catalog number	D1	D2	D21	L1	L2	L9	V	stop screw	wrench size stop screw	kg
3662754	KM80ATCHPVTTH12095M	12	24	32	95	73	36	10	TTSS10014M	5mm	1,48
3662755	KM80ATCHPVTTH12160M	12	24	32	160	63	36	10	TTSS10014M	5mm	1,96
3662756	KM80ATCHPVTTH14095M	14	27	34	95	73	36	10	TTSS10014M	5mm	1,54
3662757	KM80ATCHPVTTH16100M	16	27	34	100	78	39	10	TTSS12014M	6mm	1,55
3662758	KM80ATCHPVTTH18100M	18	33	42	100	78	39	10	TTSS12014M	6mm	1,75
3662759	KM80ATCHPVTTH18160M	18	33	42	160	70	39	10	TTSS12014M	6mm	2,45
3662760	KM80ATCHPVTTH20105M	20	33	42	105	83	41	10	TTSS16014M	8mm	1,77
3662761	KM80ATCHPVTTH25115M	25	44	53	115	93	47	10	TTSS16014M	8mm	2,34
3662762	KM80ATCHPVTTH32120M	32	44	53	120	98	51	10	TTSS16014M	8mm	2,26

(continued)

(HPV TT HT continued)

**Cutting Tool Shank Requirements
inch (industry standard)**

cutting tool shank diameter	tolerance
1/2, 9/16, 5/8, & 11/16	.0000/-.0004
3/4, 7/8, 1, & 1-1/4	.0000/-.0005

■ HPV TT HT • Inch


order number	catalog number	D1	D2	D21	L1	L2	L9	V	stop screw	wrench size stop screw	lbs
3598813	KM80ATCHPVTTH050374	1/2	.95	1.26	3.740	2.87	1.42	.39	TTSS10014M	5mm	3.25
3598814	KM80ATCHPVTTH056374	9/16	1.06	1.34	3.740	2.87	1.42	.39	TTSS10014M	5mm	3.38
3598815	KM80ATCHPVTTH062394	5/8	1.06	1.34	3.937	3.07	1.54	.39	TTSS12014M	6mm	3.41
3598816	KM80ATCHPVTTH062850	5/8	1.06	1.34	8.500	2.48	1.54	.39	TTSS12014M	6mm	5.65
3598817	KM80ATCHPVTTH075413	3/4	1.30	1.65	4.134	3.27	1.61	.39	TTSS16014M	8mm	3.93
3598818	KM80ATCHPVTTH075630	3/4	1.30	1.65	6.299	2.76	1.61	.39	TTSS16014M	8mm	5.35
3598819	KM80ATCHPVTTH088413	7/8	1.30	1.65	4.134	3.27	1.61	.39	TTSS16014M	8mm	3.84
3598820	KM80ATCHPVTTH100453	1	1.73	2.08	4.528	3.66	1.85	.39	TTSS16014M	8mm	5.14
3598821	KM80ATCHPVTTH125472	1 1/4	1.73	2.08	4.724	3.86	2.01	.39	TTSS16014M	8mm	4.99

NOTE: Do not overheat. Overheating will destroy the accuracy and functionality of the toolholder.

Shrink Fit technical section, see page M78.

Supplied with stop screw.



Adjusting stop screw gage, see page M81.

Shrink Fit accessories, see page L12–L13.

Optional M6~1.0P x 5 lg fine-balancing screw set (10 pieces) is available.

Order number is MS1276PKG and must be ordered separately.

- Tremendous Grip (3:1 advantage).



TG collet series	Collet Capacity			
	mm		inch	
	min	max	min	max
TG75	2,6	20,0	3/64	3/4
TG100	2,6	25,5	5/64	1
TG150	11,6	40,0	23/64	1-1/2

■ TG • Single-Angle Collet Chucks

order number	catalog number	collet series	D11		L1		L9		V		kg	lbs
			mm	in	mm	in	mm	in	mm	in		
3138953	KM80ATCTG075160	TG75	50	1.97	160	6.299	53	2.09	47	1.85	2,96	6.52
2022194	KM80ATCTG100394	TG100	60	2.36	100	3.937	70	2.75	—	—	2,32	5.11
2022195	KM80ATCTG150492	TG150	85	3.35	125	4.921	83	3.27	—	—	4,31	9.50

■ Spare Parts



catalog number	locknut	wrench	stop screw	wrench size stop screw	coolant cap	Nm	ft. lbs.
KM80ATCTG075160	LNA075M	HSW45M	SS081041G	4mm & 5/32	SSCC081	108-136	80-100
KM80ATCTG100394	LNA100M	HSW58M	—	—	—	163-203	120-150
KM80ATCTG150492	LNA150M	HSW80M	—	—	—	217-271	160-200

NOTE: Collet must be loaded into locknut first. Before loading into the chuck body, insert the cutting tool, then tighten to the recommended tightening torque.

Collet chuck technical section, see page M98.

Supplied with locknut and stop screw.

Locknut wrench must be ordered separately.

Interchangeable locknuts, coolant-style locknuts, and coolant disks are available and must be ordered separately; see pages L16–L17.



Stop screw coolant caps are available and must be ordered separately; see pages L34–L35.

Balanceable/interchangeable locknuts are available and must be ordered separately; see page L16.

TG standard straight-bore collets, see page J10.

TG tap collets, see page J10.

- Grip (2:1 advantage).



KM80ATC Shank Tools




ER collet series	Collet Capacity			
	mm		inch	
	min	max	min	max
ER32	2,0	20,0	.08	.81
ER40	3,0	26,0	.12	1.00

■ ER • Single-Angle Collet Chucks



order number	catalog number	collet series	D11		L1		L9		locknut	wrench				
			mm	in	mm	in	mm	in			Nm	ft. lbs.	kg	lbs
1953471	KM80ATCER3265	ER32	50	1.97	65	2.559	46,0	1.81	LNSER32M	ER32WM	136	100	1,45	3.20
2022196	KM80ATCER4090	ER40	50	1.97	90	3.543	70,3	2.77	LNSER40M	ER40WM	176	130	2,09	4.61


NOTE: Collet must be loaded into locknut first. Before loading into the chuck body, insert the cutting tool, then tighten to the recommended tightening torque.
 Collet chuck technical section, see page M98.
 Supplied with locknut.
 Locknut wrench must be ordered separately.
 Interchangeable coolant-style locknuts and coolant disks are available and must be ordered separately; see page L19.
 ER standard straight-bore collets, see page J50.
 ER tap collets, see pages J58–J59.
 ER TCT tension-only tap collets, see page J60.



■ WD • Drill Adapters with Drive



order number	catalog number	D1		L9		D2		L1		cup point socket set screw	wrench size stop screw	kg	lbs
		mm	in	mm	in	mm	in	mm	in				
3891593	KM80ATCWD32090M	32	1.260	61	2.400	62	2.435	90,0	3.543	SS03M023	6 mm	2,37	5.23
3891594	KM80ATCWD40100M	40	1.575	71	2.800	70	2.750	100,0	3.937	SS03M023	6 mm	2,80	6.18
3138896	KM80ATCWD50110M	50	1.969	71	2.795	80	3.144	110,0	4.331	SS03M023	6 mm	3,51	7.73




■ WN/EM • Whistle Notch/End Mill Combination Adapter



order number	catalog number	D1	D2	L1	L9	V	lock screw	wrench size lock screw	stop screw	stop screw wrench size	Nm	kg
3901247	KM80ATCWNE06065M	6	25	65	30	10	SS03M012	3mm	571.060	2,5mm	7	1,29
3901248	KM80ATCWNE08065M	8	28	65	30	10	SS03M014	4mm	571.067	3mm	15	1,33
3901249	KM80ATCWNE10075M	10	35	75	35	10	SS03M018	5mm	571.068	4mm	25	1,49
3901250	KM80ATCWNE12080M	12	42	80	40	10	SS03M023	6mm	571.074	5mm	35	1,68
3901251	KM80ATCWNE14080M	14	44	80	41	8	SS03M023	6mm	571.074	5mm	35	1,72
3901252	KM80ATCWNE16085M	16	48	85	44	8	SS03M025	6mm	571.075	6mm	50	1,89
3901283	KM80ATCWNE18085M	18	50	85	43	10	SS03M025	6mm	571.075	6mm	50	1,94
3901284	KM80ATCWNE20085M	20	52	85	45	10	SS03M026	8mm	571.076	6mm	95	1,98
3901285	KM80ATCWNE25100M	25	65	100	50	10	SS03M027	10mm	571.077	6mm	135	2,76
3901286	KM80ATCWNE32105M	32	72	105	55	10	SS03M029	10mm	571.077	6mm	160	3,18
3901287	KM80ATCWNE40115M	40	90	115	65	10	SS03M029	10mm	571.077	6mm	160	4,71

NOTE: Do not overtighten lock screw; use torque recommendations above.
Supplied with lock screw and stop screw.
Lock screw and stop screw wrenches are not included.




■ EM • Inch



order number	catalog number	D1	D2	L1	L9	lock screw	wrench size lock screw	ft. lbs.	lbs
2022197	KM80ATCEM100354	1	2.00	3.543	2.46	ELS075056PKG	3/8	110	4.26
2022198	KM80ATCEM125354	1 1/4	2.50	3.543	2.51	ELS075062PKG	3/8	110	5.21
1961336	KM80ATCEM150382	1 1/2	2.75	3.819	2.93	ELS075069PKG	3/8	110	5.88
2022199	KM80ATCEM200492	2	3.74	4.921	3.53	ELS100088PKG	1/2	150	11.61

NOTE: Do not overtighten lock screw; use torque recommendations above.
 Supplied with lock screw.
 Lock screw wrench not included.



■ SSF • Straight Shank Adapter for Drill Shanks with Flats





order number	catalog number	D1	L1	D2	L9	lock screw	wrench size stop screw	ft. lbs.	lbs
2024413	KM80ATCSSF075350	.750	3.500	3.150	2.250	ELS062050PKG	5/16	70	4.02
2024414	KM80ATCSSF100450	1.000	4.500	3.150	3.250	—	3/8	110	4.99
2024415	KM80ATCSSF125500	1.250	5.000	3.150	3.500	ELS075056PKG	3/8	110	6.96
2024416	KM80ATCSSF150550	1.500	5.500	3.150	4.000	ELS075056PKG	3/8	110	8.18
2024417	KM80ATCSSF200650	2.000	6.500	3.150	4.250	ELS100088PKG	1/8	150	15.93



WARNING

During through-hole operations, a slug or disk is produced as the tool breaks through the workpiece. When the drill is stationary and the workpiece is rotating, this slug may be hurled from the chuck by centrifugal force. Provide adequate shielding to protect bystanders.




■ SMC • Metric

order number	catalog number	D1	D2	D4	G1	L1	socket-head cap screw	lock screw	drive key	wrench size lock screw	kg
3897160	KM80ATCSMC22040M	22	49	—	—	40	MS1234	—	KDK22M	8mm	1,52
3897161	KM80ATCSMC27040M	27	60	—	—	40	—	KLSS27M	KDK27M	10mm	1,70
3897162	KM80ATCSMC32040M	32	78	—	—	40	—	KLSS32M	KDK32M	12mm	2,02
3897193	KM80ATCSMC40045M	40	89	67	M12 X 1.75	45	—	KLSS40M	KDK40M	12mm	2,55
3897194	KM80ATCSMC50055M	50	98	—	—	55	—	KLS50M	—	—	3,60
3897195	KM80ATCSMC60060M	60	129	102	M16 X 2.0	60	—	—	KDK60M	—	5,28

■ SMC • Inch

order number	catalog number	D1	D2	D4	G1	L1	lock screw	drive key	wrench size lock screw	lbs
3955375	KM80ATCSMC2C100158	1	2.19	—	—	1.575	KLS10	KDK06	5/16	3.52
3955376	KM80ATCSMC125158	1 1/4	2.88	—	—	1.575	KLS12	KDK08	5/16	4.26
3955377	KM80ATCSMC125394	1 1/4	2.88	—	—	3.937	KLS12	KDK08	5/16	8.49
3955378	KM80ATCSMC150158	1 1/2	3.81	—	—	1.575	KLS15	KDK10	3/8	5.46
3955379	KM80ATCSMC200216	2	4.88	4.000	.625-11 UNC	2.165	KLS20	KDK12	9/16	9.55
3955380	KM80ATCSMC250225	2 1/2	4.88	4.000	.625-11 UNC	2.250	—	KDK16	9/16	10.82
3955381	KM80ATCSMC250450	2 1/2	4.88	4.000	.625-11 UNC	4.500	—	KDK16	9/16	14.77


NOTE: Do not overtighten lock screw.
Supplied with lock screw and drive keys.
Interchangeable coolant-style lock screws are available and must be ordered separately; see page L38.
Lock screw wrench not included.



■ S • KM Extension



order number	catalog number	CSWS system size	D2		L1		wrench size			spare parts package	kg	lbs
			mm	in	mm	in	actuation screw	Nm	ft. lbs.			
2024394	KM80ATCS80120	KM80	80	3.150	120	4.724	14mm	78-84	58-64	KM80PKG3S	4,28	9.43
2024395	KM80ATCS80160	KM80	80	3.150	160	6.299	14mm	78-84	58-64	KM80PKG3S	5,82	12.82




■ S • KM Reducer



order number	catalog number	CSWS system size	D2		L1		L2		wrench size			spare parts package	kg	lbs
			mm	in	mm	in	mm	in	actuation screw	Nm	ft. lbs.			
2024396	KM80ATCS4060	KM40	40	1.575	60	2.362	38	1.496	6mm	12-16	9-12	KM40PKG3S	1,45	3.20
2024397	KM80ATCS5080	KM50	50	1.969	80	3.150	58	2.284	10mm	27-34	20-25	KM50PKG3S	1,86	4.09
2024398	KM80ATCS6380	KM63	63	2.480	80	3.150	58	2.284	12mm	47-54	35-40	KM63PKG3S	2,18	4.81


NOTE: Designed for centerline KM cutting units.



■ ES • KM Offset Reducer




order number	catalog number	CSWS system size	D2		F		L1		wrench size			spare parts package	kg	lbs
			mm	in	mm	in	mm	in	actuation screw	Nm	ft. lbs.			
2203620	KM80ATCESL63105	KM63	80	3.150	20	.787	105	4.134	12mm	47-54	35-40	KM63PKG3S	3,87	8.50
2048377	KM80ATCESR63105	KM63	80	3.150	20	.787	105	4.134	12mm	47-54	35-40	KM63PKG3S	3,87	8.50



■ BN • Blank

order number	catalog number	D2		L1		hardness range	kg	lbs
		mm	in	mm	in			
2873209	KM80ATCBN125075M	125	4.921	75	2.953	32-38 HRC	6,20	13.68
2879350	KM80ATCBN140130M	140	5.512	130	5.118	32-38 HRC	14,11	31.11



■ PSC-KM



order number	catalog number	CSMS system size	CSWS system size	D2	L1	L2	wrench size actuation screw	Nm	ft. lbs.	KM spare parts package	kg	lbs
3852030	PSC63KM40TS065M	PSC63	KM40TS	40	65	43	6 mm	12	9	KM40PKG3S	1,09	2.41
3852063	PSC63KM40TS090M	PSC63	KM40TS	40	90	68	6 mm	12	9	KM40PKG3S	1,32	2.91
3874895	PSC80KM50TS070M	PSC80	KM50TS	50	70	40	10 mm	27	20	KM50PKG3S	2,16	4.77
3852064	PSC63KM50TS090M	PSC63	KM50TS	50	90	68	10 mm	27	20	KM50PKG3S	1,59	3.50
3852031	PSC63KM50TS075M	PSC63	KM50TS	50	75	53	10 mm	27	20	KM50PKG3S	1,37	3.03
3874897	PSC80KM50TS100M	PSC80	KM50TS	50	100	70	10 mm	27	20	KM50PKG3S	2,61	5.76
3864845	PSC80KM63TS155M	PSC80	KM63TS	63	155	125	12 mm	47	35	KM63PKG3S	4,35	9.59
3852065	PSC63KM63TS105M	PSC63	KM63TS	63	105	105	12 mm	47	35	KM63PKG3S	2,34	5.17
3864844	PSC80KM63TS080M	PSC80	KM63TS	63	80	50	12 mm	47	35	KM63PKG3S	2,57	5.67
3852032	PSC63KM63TS090M	PSC63	KM63TS	63	90	90	12 mm	47	35	KM63PKG3S	2,00	4.42
3874898	PSC80KM80TS155M	PSC80	KM80TS	80	155	155	14 mm	79	58	KM80PKG3S	5,89	12.99
3874896	PSC80KM80TS090M	PSC80	KM80TS	80	90	90	14 mm	79	58	KM80PKG3S	3,40	7.49